



Revised
November 14th,
2006

14101 Botts Road • Grandview, Missouri 64030
Tel. 1-800-552-3131 • (816) 778-0521
Fax 1-800-619-4577 • (816) 778-0515

EMERGENCY PHONE 1-800-255-3924

MATERIAL SAFETY DATA SHEET

**RP, SI, FS, HT, MG SERIES
CYANOACRYLATE ADHESIVE**

HMIS	HEALTH	2	FLAMMABILITY	2	REACTIVITY	2
NFPA	HEALTH	2	FIRE HAZARD	2	REACTIVITY	2

New Glue -GLU-100.00

1. Chemical Product

Product Name: RP, SI, FS, HT, MG Series
Product Type: Ethyl-2-Cyanoacrylate Ester
Molecular Formula: C6H7NO2

2. Composition and Information on Harmful Ingredients

Ingredients	CAS No.	OSHA PEL	ACGIH TLV	Other Limits	%Composition
Ethyl-2-Cyanoacrylate	7085-85-0	N/A	0.2ppm (TWA)	0.3ppm (STEL)	86-99.99

3. Hazards Identification

Label Precautionary Statements: Irritant. Irritating to eyes, skin, and respiratory system. Cyanoacrylate. Danger. Bonds skin and eyes in seconds.

Primary Routes of Entry: None Known

Symptoms of Exposure: Vapor highly irritating to eyes and breathing. Prolonged exposure may lead to non-allergic asthma.

Medical Conditions Aggravated by Exposure: No applicable information found.

Ethyl Cyanoacrylate is not listed as a carcinogen in the US National Toxicology Program Annual report on carcinogens, or by the International Agency for Research on Cancer.

4. First Aid Measures

Ingestion: Ingestion not likely due to polymerization.

Inhalation: Remove to fresh air, if symptoms continue, seek medical advice.

Skin Contact: Soak in warm soapy water.

Eye Contact: Flush with water, seek medical attention.

MATERIAL SAFETY DATA SHEET
RP, SI, FS, HT, MG SERIES
CYANOACRYLATE ADHESIVE

5. Fire Fighting Measures

Flash Point:	>81°C (150-200°F)
Extinguishing Media:	Water spray, foam, dry chemical or CO2
Special Fire Fighting Procedures:	Wear self contained breathing apparatus
Unusual Fire / Explosion Hazards:	No applicable information found.
Hazardous Thermal Decomposition Products:	Irritating organic vapors may be formed

6. Accidental Release Measures

Ventilate area of spill, flood with water to polymerize, absorb with sand / earth and dispose to chemical waste bin. Dispose in accordance with pertinent national legislation.

7. Handling and Storage

When using large volumes ensure that operational area is well ventilated.
Store between 5-25°C; avoid strong light and heat sources.
Incompatible with amine, bases, water.
Avoid skin contact and inhalation of vapor.

8. Exposure Control and Personal Protection

Eye Protection:	Safety goggles / glasses suitable for use with chemicals.
Respiratory Protection:	Always use appropriate filter mask / respirator.
Skin Protection:	Nitrile / polyethylene gloves, coveralls, avoid cotton products.
Ventilation:	Good general or local exhaust ventilation is required for usage.

9. Physical and Chemical Properties

Form:	Liquid
Color:	Water white / straw colored
Odor:	Sharp, irritating
Solubility in Water:	Immiscible in water
Boiling Point:	>100°C
Specific Gravity @ 25°C:	1.1
Vapor Pressure @ 25°C:	<0.5mm Hg
Flash Point:	>81°C
V.O.C. Content:	Less than 20g/L estimated (California SCAQMD Method 316B)

10. Reactivity and Stability

Stability:	Stable
Hazardous Polymerization:	Will not occur
Incompatibility:	Water, bases, amines
Conditions to Avoid:	No applicable information found
Hazardous Decomposition Products:	No applicable information found

